
SUBSET 04 - STRUCTURE

INDEX OF DRAWINGS


DRAWING NUMBER	DRAWING TITLE	DRAWING NUMBER	DRAWING TITLE
S-1	STRUCTURE INDEX	S-21	PIER 3
S-2	PLAN & ELEVATION	S-22	PIER 4
S-3	TYPICAL SECTION AND PROFILE	S-23	PIER 5
S-4	CONSTRUCTION STAGING 1	S-24	PIER 6
S-5	CONSTRUCTION STAGING 2	S-25	SUBSTRUCTURE CONCRETE REPAIRS
S-6	STAGE 1 DEMOLITION PLAN	S-26	KEEPER BLOCK DETAILS 1
S-7	STAGE 1 CONSTRUCTION PLAN	S-27	KEEPER BLOCK DETAILS 2
S-8	STAGE 2 DEMOLITION PLAN	S-28	KEEPER BLOCK DETAILS 3
S-9	STAGE 2 CONSTRUCTION PLAN	S-29	KEEPER BLOCK DETAILS 4
S-10	DECK REPAIR PLAN	S-30	PARAPET MODIFICATION DETAILS
S-11	UNDERSIDE OF DECK REPAIR PLAN	S-31	ABUTMENT MODIFICATIONS 1
S-12	DECK CONCRETE REPAIRS	S-32	ABUTMENT MODIFICATIONS 2
S-13	LINK SLAB DETAILS	S-33	ABUTMENT MODIFICATIONS 3
S-14	FRAMING PLAN	S-34	MISC. DETAILS
S-15	STEEL REPAIR DETAILS	S-35	HIGHWAY GUARDRAIL TRANSITION DETAILS 1
S-16	BEARING DETAILS	S-36	HIGHWAY GUARDRAIL TRANSITION DETAILS 2
S-17	ABUTMENT 1	S-37	HIGHWAY GUARDRAIL TRANSITION DETAILS 3
S-18	ABUTMENT 2	S-38	DRAINAGE DETAILS 1
S-19	PIER 1	S-39	DRAINAGE DETAILS 2
S-20	PIER 2	S-40	PRESSURE RELIEF JOINT



						DE:
-	-	-	-		THE INFORMATION, INCLUDING ESTIMATED	
-	-	-	-		QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED	СН
-	-	-	-		INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE	
-	-	-	-		THE CONDITIONS OF ACTUAL QUANTITIES	
-	-	-	-		OF WORK WHICH WILL BE REQUIRED.	
-	_	-	-			
REV.	DATE	REVISION DESCRIPTION	SHEET	NO.	Plotted Date: 11/19/2014]

SCALE AS NOTED






REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 **OVER I-84 EB AND I-84 TR 833**

TOWN:	
EAST	HARTFORD
DRAWING TITLE:	

042-305 PRAWING NO.

S-1 02.04.01

STRUCTURE INDEX



INSPECTION	OF	FIE
METHODS		T

ULTRASONIC

MAGNETIC PARTICL

- FIELD WELDS							
	UNIT	QUANTITY	TRANSPOR	WEIGHTS			
	INCH		MEMBER	LENGTH	HEIGHT	WIDTH	MASS
LE	FEET		NONE	NONE	NONE	NONE	NONE

BLOCK:

GENERAL NOTES:

SPECIFICATIONS:

CONNECTICUT DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FORM 816 (2004), SUPPLEMENTAL SPECIFICATIONS DATED JULY 2014 AND SPECIAL PROVISIONS.

DESIGN SPECIFICATIONS:

AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS SIXTH EDITION, INCLUDING 2013 INTERIM REVISIONS AS SUPPLEMENTED BY THE CONNECTICUT DEPARTMENT OF TRANSPORTATION BRIDGE DESIGN MANUAL (2003 EDITION), UP TO AND INCLUDING 2011 REVISIONS.

DESIGN STRENGTHS:

CLASS "S" CONCRETEf'c = 3.0 K	(SI
CLASS "F" CONCRETEf'c = 4.0 K	
REINFORCEMENT (ASTM A615 GRADE 60)fy = 60 K	SI
STRUCTURAL STEEL (ASTM M270, GRADE 50T2)	SI

THE SPECIFIED CONCRETE STRENGTH USED IN DESIGN, f'c, OF THE CONCRETE COMPONENTS IS NOTED ABOVE. THE MINIMUM COMPRESSIVE STRENGTH OF THE CONCRETE IN THE CONSTRUCTED COMPONENTS SHALL CONFORM TO THE REQUIREMENTS OF THE SUPPLEMENTAL SPECIFICATION "SECTION 6.01 CONCRETE FOR STRUCTURES".

LIVE LOAD:

SUPERSTRUCTURE STANDARD DESIGN VEHICLE: AASHTO HL93

FUTURE PAVING ALLOWANCE

NONE

STRUCTURAL STEEL:

SEE STRUCTURE SHEET NOTES FOR DESIGNATIONS AND REQUIREMENTS.

BITUMINOUS CONCRETE OVERLAY:

THIS SHALL CONSIST OF TWO LIFTS. THE FIRST SHALL BE 1" THICK BOTTOM COURSE OF HMA S0.25 AND THE SECOND SHALL BE $1\frac{1}{2}$ " THICK TOP COURSE OF HMA S0.375 FOR A TOTAL OF $2\frac{1}{2}$ ".

DIMENSIONS:

ALL DIMENSIONS SHOWN ON THE PLANS ARE IN FEET AND INCHES EXCEPT IF NOTED OTHERWISE. ALL ELEVATIONS ARE GIVEN IN FEET. WHEN DECIMAL DIMENSIONS ARE GIVEN TO LESS THAN THREE DECIMAL PLACES, THE OMITTED DIGITS SHALL BE ASSUMED TO BE ZEROES.

EXISTING DIMENSIONS:

DIMENSIONS OF THE EXISTING STRUCTURE SHOWN ON THESE PLANS ARE FOR THE GENERAL REFERENCE ONLY. THEY HAVE BEEN TAKEN FROM THE ORIGINAL DESIGN DRAWINGS AND ARE NOT GUARANTEED. THE CONTRACTOR SHALL TAKE ALL FIELD MEASUREMENTS NECESSARY TO ASSURE PROPER FIT OF THE FINISHED WORK AND SHALL ASSUME FULL RESPONSIBILITY FOR THEIR ACCURACY. WHEN SHOP DRAWINGS BASED ON FIELD MEASUREMENTS ARE SUBMITTED FOR APPROVAL THE FIELD MEASUREMENT SHALL ALSO BE SUBMITTED FOR REFERENCE BY THE REVIEWER.

COMPOSITE CONSTRUCTION:

CONSTRUCTION LOADS AND DEAD LOADS WILL BE PERMITTED ON THE DECK WHEN DIRECTED BY THE ENGINEER BUT ONLY WHEN THE CONCRETE HAS REACHED A STRENGTH OF f'c = 3500 PSI. LIVE LOADS (TRAFFIC) WILL BE PERMITTED ON THE STRUCTURE AFTER THE CONCRETE HAS REACHED A STRENGTH OF f'c = 4000 PSI.

CLASS "S" CONCRETE:

CLASS "S" CONCRETE SHALL BE USED FOR THE SUBSTRUCTURE REPAIRS.

CLASS "F" CONCRETE:

CLASS "F" CONCRETE SHALL BE USED FOR THE APPROACH SLABS, PARAPETS, END BLOCKS, KEEPER BLOCKS AND BRIDGE DECK, INCLUDING PATCHES, UNLESS OTHERWISE SPECIFIED IN THE SPECIAL PROVISIONS.

JOINT SEAL:

SEE SILICONE EXPANSION JOINT SYSTEM SPECIAL PROVISION.

EXPOSED EDGES:

EXPOSED EDGES OF CONCRETE SHALL BE BEVELED 1" BY 1" UNLESS DIMENSIONED OTHERWISE.

CONCRETE COVER:

ALL REINFORCMENT SHALL HAVE TWO INCHES COVER UNLESS DIMENSIONED OTHERWISE.

REINFORCMENT:

ALL REINFORCMENT SHALL BE ASTM A615 GRADE 60.

EPOXY COATED REINFORCING BARS:

ALL REINFORCEMENT IN THE SUPERSTRUCTURE INCLUDING THE CONCRETE LINK SLAB, APPROACH SLAB, AND THE PARAPETS SHALL BE EPOXY COATED UNLESS OTHERWISE NOTED. THESE BARS SHALL BE INCLUDED IN THE PAY ITEM FOR "DEFORMED STEEL BARS (EPOXY COATED)".

CLOSED CELL ELASTOMER:

THE COST OF FURNISHING AND INSTALLING CLOSED CELL ELASTOMER SHALL BE INCLUDED IN THE COST OF THE ITEM "CLASS 'F' CONCRETE."

CONSTRUCTION JOINTS:

CONSTRUCTION JOINTS, OTHER THAN THOSE SHOWN ON THE PLANS, WILL NOT BE PERMITTED WITHOUT THE PRIOR APPROVAL OF THE ENGINEER.

-	-	-	-	THE INFORMATION, INCLUDING ESTIMATED
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
-	-	-	-	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES
-	-	-	-	OF WORK WHICH WILL BE REQUIRED.
-	-	-	-	

REVISION DESCRIPTION

REV. DATE

SCALE AS NOTED

MUST BE GIVEN TO INSPECTING THE FOLLOWING SPECIAL COMPONENTS AND DETAILS (THE LISTING FOR COMPONENTS FOR SPECIFIC ATTENTION SHALL NOT

BE CONSTRUED TO REDUCE THE IMPORTANCE OF INSPECTION OF ANY OTHER

DETAIL

NONE

COMPONENT OF THE STRUCTURE). THE FREQUENCY OF INSPECTION OF THIS STRUCTURE SHALL BE IN ACCORDANCE WITH THE GOVERNING MANUALS FOR

BRIDGE INSPECTION, UNLESS OTHERWISE DIRECTED BY THE MANAGER OF

BRIDGE SAFETY AND EVALUATION.


COMPONENT

NONE

SHEET NO. Plotted Date: 11/19/2014



Filename: ...\S-02 - Plan and Elevation.dgn




REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 **OVER I-84 EB AND I-84 TR 833**

	EAST	HARTFORD
DRAWING	TITLE:	

S-2 02.04.02

042-305

PLAN & ELEVATION




BETWEEN BEARINGS

AT BEARINGS

TYPICAL REHABILITATED CROSS SECTION

SCALE: $\frac{3}{8}$ " = 1'-0"



NOTE: STATIONS AT ABUTMENTS ARE AT THE EXISTING BEARING CENTERLINES.

PROFILE - SR 500 TR 801 BASELINE

HORIZONTAL SCALE: 1" = 50'-0" VERTICAL SCALE: 1" = 10'-0"

TABLE OF QUANTITIES DESCRIPTION QUANTITY LEAD COMPLIANCE FOR MISCELLANEOUS EXTERIOR TASKS LS CY 80 EARTH EXCAVATION REMOVAL OF HMA WEARING SURFACE SY 1800 TON 175 HMA S0.375 TON 120 HMA S0.25 200 MATERIAL FOR TACK COAT SY 150 PRESSURE RELIEF JOINT REMOVAL OF CONCRETE DECK (BRIDGE) SY 500 EΑ JACKING FOR BEARING REPLACEMENT EΑ DOWNSPOUT SPLASH PAD SHEAR CONNECTORS LS LS EΑ CONSTRUCT WEEP DRAINS BRIDGE SCUPPER - FIBERGLASS HOPPER EΑ 8" PIPE FOR BRIDGE DRAINAGE (FIBERGLASS) 150 LF 1-1/2" POLYVINYL CHLORIDE PLASTIC PIPE LF SILICONE EXPANSION JOINT SYSTEM 150 BEARING REPLACEMENT WITH ELASTOMERIC BEARING PADS EΑ EΑ 84 STEEL-LAMINATED ELASTOMERIC BEARINGS 240 ROADWAY PARAPET WALL LF MODIFY BRIDGE PARAPET 660 900 BRIDGE PARAPET CAP EΑ RECONSTRUCT BRIDGE ENDBLOCK CF 200 CLASS "S" CONCRETE 85 FULL DEPTH PATCH (CLASS "F" CONCRETE) CY CY 200 CLASS "F" CONCRETE CF 1215 PARTIAL DEPTH PATCH 1" PREFORMED EXPANSION JOINT FILLER FOR BRIDGES SF 50 650 LF EPOXY INJECTION CRACK REPAIR DEFORMED STEEL BARS - EPOXY COATED LBS 30000 DRILLING HOLES AND GROUTING DOWELS EΑ 340 LS DEBRIS SHIELD LS STRUCTURAL STEEL REPAIRS (SITE NO. 2) TEMPORARY SLAB SUPPORT (SITE NO. 2) CONTAINMENT AND COLLECTION OF SURFACE PREPARATION DEBRIS (SITE NO. 2) STRUCTURAL STEEL - MISCELLANEOUS CWT | 15 SF 1880 LOCALIZED PAINT REMOVAL AND FIELD PAINTING OF EXISTING STEEL 1885 MEMBRANE WATERPROOFING (WOVEN GLASS FABRIC) SY CY REMOVAL OF EXISTING MASONRY 1340 CONCRETE HAUNCH REMOVAL LF 100 2" RIGID METAL CONDUIT IN STRUCTURE 450 REMOVE CONDUIT LF 350 REMOVE CABLE LF

					D
-	-	-	ı	THE INFORMATION, INCLUDING ESTIMATED	
-	-	-	ı	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED	С
-	-	-	-	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE	
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES	Γ
-	-	-	-	OF WORK WHICH WILL BE REQUIRED.	l
-	-	-	-		l


SHEET NO. Plotted Date: 11/19/2014

REVISION DESCRIPTION


REV. DATE

SCALE AS NOTED





/N:	PROJECT NO.
	042-305
EAST HARTFORD WING TITLE:	DRAWING NO.
TYPICAL SECTION AND PROFILE	SHEET NO. 02.04.03



STAGE 1 CONSTRUCTION - OUTSIDE LIMITS OF LINK SLAB

SCALE: $\frac{3}{8}$ " = 1'-0"

BRIDGE OUT TO OUT VARIES (SPAN 2 SHOWN = 44'-6") 28'-1" LIMITS OF STAGE 2 WORK ZONE (SPAN 2 SHOWN) 16'-5" (SPAN 2 SHOWN) LIMITS OF CONSTRUCTION OF BITUMINOUS CONCRETE ___ 1'-0" SHOULDER AND MEMBRANE WATERPROOFING 1'-0" SHOULDER — 1'-7" LIMITS OF REMOVAL OF BITUMINOUS CONCRETE 8'-3" 11'-0" TRAVEL LANE AND MEMBRANE WATERPROOFING REMOVE STEEL RAIL CONSTRUCT MODIFIED PARAPET CAP (SEE DETAIL ON DRAWING NO. S-30) EXISTING 2" RMC -IN SPANS 1&2 TO -B SR 500 TR 801 CONSTRUCT PARAPET MODIFICATION REMAIN OPERATIONAL (SEE DETAIL ON DRAWING NO. S-30) **THROUGHTOUT** CONSTRUCTION - REMOVE CURB REMOVE AND REPLACE EXISTING BITUMINOUS CONCRETE AND TEMPORARY PRECAST CONCRETE MEMBRANE WATERPROOFING BARRIER CURB (STRUCTURE) - MODIFY HAUNCHES WITHIN LIMITS - REPAIR TOP AND UNDERSIDE STAGE 2 CONSTRUCTION (TYP.) OF DECK AS NOTED ON (SEE DETAIL ON DRAWING NO. S-12) DRAWING NO. S-10 THRU S-12 DEBRIS SHIELDING TO BE DESIGNED <u>LEGEND</u> AND PROVIDED BY CONTRACTOR EXISTING CONCRETE, WEARING SURFACE AND DURING CONSTRUCTION AND SHALL MEMBRANE WATERPROOFING TO BE REMOVED BE PAID FOR UNDER ITEM 0602971A (TYP.)

STAGE 2 CONSTRUCTION - OUTSIDE LIMITS OF LINK SLAB

SCALE: $\frac{3}{8}$ " = 1'-0"

STAGE 1 NOTES - OUTSIDE LIMITS OF LINK SLABS:

- 1. SET STAGE 1 TEMPORARY TRAFFIC BARRIERS 2'-6" WEST OF SR 500 TR 801 BASELINE, AS SHOWN ON PLANS. STAGE 1 TRAFFIC BARRIERS TO BE CRASH TESTED BOLT-DOWN BARRIERS. CONTRACTOR SHALL MAINTAIN THE INTEGRITY OF THE DECK DURING SETUP AND REMOVAL OF TEMPORARY BARRIERS AND INCLUDE RESTORATION OF DECK AT ANCHOR BOLT LOCATIONS AS PART OF THE DECK REPAIR WORK.
- 2. MAINTAIN SINGLE LANE OF TRAFFIC ON WEST SIDE OF BRIDGE DURING STAGE 1 DEMOLITION AND CONSTRUCTION.
- 3. DURING STAGE 1 DEMOLITION, REMOVE STEEL BRIDGE RAIL, SAFETY WALK, HAUNCHES AND WEARING SURFACE (INCLUDING MEMBRANE WATERPROOFING) UP TO SR 500 TR 801 BASELINE (SEE DRAWING NO. S-6). ONCE WEARING SURFACE IS REMOVED, TOP AND UNDERSIDE OF DECK DEFICIENCIES INDICATED ON DRAWING NO. S-10 AND S-11 SHALL BE FIELD VERIFIED (SEE NOTE 2 ON DRAWING NO. S-12). CONTRACTOR SHALL REMOVE A PORTION OF THE ABUTMENT BACKWALLS TO ACCOMMODATE THE PROPOSED APPROACH SLABS AND SILICONE EXPANSION JOINT SYSTEM (FOR DETAILS SEE DRAWING NO. S-31).
- 4. DURING STAGE 1 CONSTRUCTION, INSTALL SILICONE EXPANSION JOINT SYSTEM, SET PROPOSED APPROACH SLABS, CAST PARAPET CAP AND CURB AND PLACE PROPOSED WEARING SURFACE (INCLUDING MEMBRANE WATERPROOFING) UP TO SR 500 TR 801 BASELINE (SEE DRAWING NO. S-7).

STAGE 2 NOTES - OUTSIDE LIMITS OF LINK SLABS:

CONSTRUCTION.

- 5. SET STAGE 2 TEMPORARY TRAFFIC BARRIERS 8'-3" EAST OF SR 500 TR 801 BASELINE SHOWN ON PLANS. STAGE 2 TRAFFIC BARRIERS TO BE CRASH TESTED LINKED BARRIERS.
- 6. MAINTAIN SINGLE LANE OF TRAFFIC ON EAST SIDE OF BRIDGE DURING STAGE 2 DEMOLITION AND
- 7. DURING STAGE 2 DEMOLITION, REMOVE STEEL BRIDGE RAIL, SAFETY WALK, HAUNCHES AND WEARING SURFACE (INCLUDING MEMBRANE WATERPROOFING) UP TO SR 500 TR 801 BASELINE (SEE DRAWING NO. S-8). ONCE WEARING SURFACE IS REMOVED, TOP AND UNDERSIDE OF DECK DEFICIENCIES INDICATED ON DRAWING NO. S-10 AND S-11 SHALL BE FIELD VERIFIED (SEE NOTE 2 ON DRAWING NO. S-12). CONTRACTOR SHALL REMOVE A PORTION OF THE ABUTMENT BACKWALLS TO ACCOMMODATE THE PROPOSED APPROACH SLABS AND SILICONE EXPANSION JOINT SYSTEM (FOR DETAILS SEE DRAWING NO. S-31).
- 8. DURING STAGE 2 CONSTRUCTION, INSTALL SILICONE EXPANSION JOINT SYSTEM, SET PROPOSED APPROACH SLABS, CAST PARAPET CAP AND CURB AND PLACE PROPOSED WEARING SURFACE (INCLUDING MEMBRANE WATERPROOFING) UP TO SR 500 TR 801 BASELINE (SEE DRAWING NO. S-9).

					DE
	-	-	-	THE INFORMATION, INCLUDING ESTIMATED	
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED	CH
-	ı	-	-	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE	
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES	
-	•	-	-	OF WORK WHICH WILL BE REQUIRED.	ĺ
-	-	-	-		ĺ
REV.	DATE	REVISION DESCRIPTION	SHEET NO.	Plotted Date: 11/19/2014	


DESIGNER/DRAFTER:


A. STUER

CHECKED BY:

C. D'ANNUNZIO

SCALE AS NOTED





BLOCK:


REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 OVER I-84 EB AND I-84 TR 833


	EAST	HARTFORD	
AWING	CONS	STRUCTION	

STAGING 1

S-4
SHEET NO.
02.04.04

042-305





STAGE 1 NOTES - WITHIN LIMITS OF LINK SLABS:

1. SET STAGE 1 TEMPORARY TRAFFIC BARRIERS 2'-6" WEST OF SR 500 TR 801 BASELINE SHOWN ON PLANS. STAGE 1 TRAFFIC BARRIERS TO BE CRASH TESTED BOLT-DOWN BARRIERS.

2. MAINTAIN SINGLE LANE OF TRAFFIC ON WEST SIDE OF BRIDGE DURING STAGE 1 DEMOLITION AND CONSTRUCTION.

- 3. DURING STAGE 1 DEMOLITION, REMOVE PARAPETS, HAUNCHES, SCUPPERS, DECK AND WEARING SURFACE (INCLUDING MEMBRANE WATERPROOFING) UP TO SR 500 TR 801 BASELINE (SEE DRAWING NO. S-6). EXISTING DECK REINFORCEMENT TO REMAIN AS INDICATED ON LINK SLAB DETAIL (SEE DRAWING NO. S-13). CARE SHALL BE TAKEN NOT TO DAMAGE EXISTING DECK REINFORCEMENT THAT IS INDICATED TO REMAIN DURING THE REMOVAL OF THE EXISTING DECK. CONTRACTOR SHALL TEMPORARILY SUPPORT DECK OVERHANG AS NECESSARY FOR STAGED CONSTRUCTION OF LINK SLAB.
- 4. DURING STAGE 1 CONSTRUCTION, CONSTRUCT LINK SLABS, REPLACE SCUPPERS, CAST PARAPETS TO MATCH MODIFIED PARAPET GEOMETRY, AND CONSTRUCT PARAFFIN JOINTS UP TO LIMITS OF SR 500 TR 801 (SEE DRAWING NO. S-7).


STAGE 2 NOTES - WITHIN LIMITS OF LINK SLABS:


5. SET STAGE 2 TEMPORARY TRAFFIC BARRIERS 8'-3" EAST OF SR 500 TR 801 BASELINE SHOWN ON PLANS. STAGE 2 TRAFFIC BARRIERS TO BE CRASH TESTED LINKED BARRIERS.


6. MAINTAIN SINGLE LANE OF TRAFFIC ON EAST SIDE OF BRIDGE DURING STAGE 2 DEMOLITION AND CONSTRUCTION.


- 7. DURING STAGE 2 DEMOLITION, REMOVE PARAPETS, HAUNCHES, SCUPPERS, DECK AND WEARING SURFACE (INCLUDING MEMBRANE WATERPROOFING) UP TO SR 500 TR 801 (SEE DRAWING NO. S-8). EXISTING DECK REINFORCEMENT TO REMAIN AS INDICATED ON LINK SLAB DETAIL (SEE DRAWING NO. S-13). CARE SHALL BE TAKEN NOT TO DAMAGE EXISTING DECK REINFORCEMENT THAT IS INDICATED TO REMAIN DURING THE REMOVAL OF THE EXISTING DECK. CONTRACTOR SHALL TEMPORARILY SUPPORT DECK OVERHANG AS NECESSARY FOR STAGED CONSTRUCTION OF LINK SLAB.
- 8. DURING STAGE 2 CONSTRUCTION, CONSTRUCT LINK SLABS, REPLACE SCUPPERS, CAST PARAPETS TO MATCH MODIFIED PARAPET GEOMETRY, AND CONSTRUCT PARAFFIN JOINTS UP TO SR 500 TR 801 (SEE DRAWING NO. S-9).


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED.	A. STUER CHECKED BY: C. D'ANNUNZIO SCALE AS NOTED	STATE OF CONNECTICUT DEPARTMENT OF TRANSPORTATION SIGNATURE/BLOCK: SIGNATURE/BLOCK:	C&C Consulting Engineers, LLC 214 Lincoln Street Boston, MA 02134	REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 OVER I-84 EB AND I-84 TR 833	EAST HARTFORD DRAWING TITLE: CONSTRUCTION STAGING 2	PROJECT NO. 042-305 DRAWING NO. S-5 SHEET NO. 02.04.05
REV. DATE REVISION DESCRIPTION SHEET NO. Plotted Date: 11/19/2014		Filename:\S-05 - Construction Staging 2.dgn			STAULING Z	


















DETAILS FOR CONCRETE HAUNCH REMOVAL

SCALE: 1'' = 1'-0''





EXISTING CONDITION

FINAL CONDITION

DETAILS FOR CONCRETE HAUNCH REMOVAL - INACCESSIBLE LOCATIONS (SEE NOTE 15)

SCALE: 1'' = 1'-0''





TYPICAL DETERIORATED REINFORCING BAR REPAIR DETAIL SCALE: 1'' = 1'-0''

CONCRETE DECK PATCH - GENERAL NOTES:

- ALL CONCRETE REPAIR MATERIALS SHALL BE IN ACCORDANCE WITH SPECIFICATIONS PROVIDED IN THE SPECIAL PROVISION FOR ITEM 0601193A "PARTIAL-DEPTH PATCH" AND ITEM 0601188 "FULL DEPTH PATCH"
- 2. AFTER THE EXISTING WEARING SURFACE AND MEMBRANE WATERPROOFING ARE REMOVED, THE CONTRACTOR SHALL PROVIDE THE ENGINEER CLEAR ACCESS TO THE BRIDGE DECK BEFORE ANY PORTION OF THE CONCRETE DECK IS REMOVED. THE ENGINEER WILL PERFORM AN INSPECTION OF THE STRUCTURAL SLAB AND DESIGNATE THE EXTENT, LOCATION AND TYPE OF REPAIR REQUIRED.

CONCRETE DECK PATCH - PARTIAL-DEPTH NOTES:

- ALL PARTIAL DEPTH PATCHES AND UNDERSIDE OF DECK REPAIRS (POP-OUTS) SHALL BE PAID FOR UNDER ITEM 0601193A "PARTIAL DEPTH PATCH". SEE SPECIAL PROVISIONS FOR ACCEPTABLE MATERIALS AND METHODS.
- 4. PARTIAL-DEPTH PATCHES SHALL BE USED IN AREAS WHERE SOUND CONCRETE IS REACHED 1" DEPTH MAXIMUM BEYOND THE REINFORCING STEEL. CONCRETE SHALL BE REMOVED TO A MINIMUM DEPTH OF 1" BELOW THE REINFORCING STEEL OR UP TO 50% OF THE CONCRETE DECK THICKNESS. REPAIRS THAT REQUIRE REMOVAL OF MORE THAN 50% OF THE CONCRETE DECK THICKNESS SHALL BE FULL-DEPTH PATCHES.
- PARTIAL-DEPTH PATCHES SHALL NOT BE USED FOR OVERHEAD APPLICATIONS. IF DETERIORATION IN THE UNDERSIDE OF THE DECK COMPLETELY EXPOSES THE REINFORCEMENT FOR AN AREA EQUAL TO OR GREATER THAN 5 SF, THE AREA SHALL BE TREATED WITH A FULL-DEPTH REPAIR. IF THE DETERIORATION IN THE UNDERSIDE OF DECK COMPLETELY EXPOSES THE REINFORCEMENT FOR AN AREA LESS THAN 5 SF OR IF THE REINFORCEMENT IS STILL PARTIALLY ENCASED IN CONCRETE, THE REBAR SHALL BE CLEANED AND EPOXY COATING SHALL BE APPLIED TO THE EXPOSED STEEL AREAS.

<u> CONCRETE DECK PATCH - FULL-DEPTH NOTES:</u>

REMOVE SOUND CONCRETE AS REQUIRED TO OBTAIN MINIMUM VERTICAL SLOPE OF 4 VERTICAL TO 1 HORIZONTAL (TYP.)

CONCRETE DECK PATCH - SURFACE PREPARATION NOTES:

- 7. CUT ALONG NEAT LINES AROUND REPAIR AREA PRIOR TO CONCRETE EXCAVATION. USE CUT DEPTH OF $\frac{1}{2}$ " OR LESS AS REQUIRED TO AVOID CUTTING REINFORCING STEEL
- IF REINFORCING STEEL IS EXPOSED, CLEAN EXPOSED STEEL AND SURROUNDING CONCRETE AS SPECIFIED IN THE SPECIAL PROVISIONS FOR "PARTIAL-DEPTH PATCH".
- THE CONTRACTOR SHALL ENSURE THAT ALL BOND INHIBITING MATERIALS (DIRT, GREASE, LOOSELY BONDED AGGREGATE) HAVE BEEN REMOVED IMMEDIATELY PRIOR TO PATCHING.
- 10. WET CONCRETE REPAIR AREA SO THAT SUBSTRATE IS SATURATED SURFACE DRY WITH NO STANDING WATER. WATER USED TO PREPARE AND WET THE SURFACE SHALL CONTAIN NO DETERGENTS OR BOND INHIBITING CHEMCALS.

CONCRETE DECK PATCH - CONSTRUCTION NOTES:

- 11. A NEW REINFORCING BAR (EPOXY COATED) SHALL BE PLACED TO SUPPLEMENT AN EXISTING REINFORCING BAR WHEN AN EXISTING BAR HAS A SECTION LOSS OF 25% OR MORE OF THE ORIGINAL CROSS SECTION, AS DETERMINED BY THE ENGINEER, OR THE EXISTING REINFORCEMENT IS BROKEN. THE NEW REINFORCING BAR SHALL EXTEND 32 BAR DIAMETERS PAST LOCATIONS WHERE SECTION LOSS OR BREAK IS OBSERVED AND SHALL BE PLACED AT THE SAME LEVEL ALONG THE DETERIORATED OR BROKEN BAR, IN LIEU OF SUPPLEMENTING A BAR ADJACENT TO A DETERIORATED BAR, THE CONTRACTOR MAY CUT OUT THE DETERIORATED BAR AND MECHANICALLY SPLICE THE NEW BAR TO EXISTING REINFORCEMENT
- 12. THE TOP OF DECK SURFACE FOR ALL PATCHES SHALL BE EVEN WITH THE ADJACENT EXISTING DECK SLAB AND MAINTAIN THE EXISTING GRADES AND CROSS SLOPES. HUMPS OR SAGS IN THE PATCH EXCEEDING $\frac{1}{8}$ " SHALL BE GROUND DOWN OR REPAIRED PRIOR TO PLACEMENT OF PROPOSED MEMBRANE WATERPROOFING AND WEARING SURFACE.
- 13. DECK REINFORCEMENT AND CONCRETE PATCH DETAILS PROVIDED ON THIS SHEET ARE GENERAL. ACTUAL REINFORCEMENT SIZE AND SPACING WILL VARY FROM LOCATION TO LOCATION.

ABOVE DIAPHRAGMS OR AS APPROVED OF BY THE ENGINEER.

HAUNCH REMOVAL NOTES:

- 14. ALL HAUNCHES SHALL BE REMOVED AS PART OF THE BRIDGE REHABILITATION. 15. SAW CUTTING IS NOT REQUIRED FOR HAUNCH REMOVAL ONLY IN AREAS HAVING INSUFFICIENT CLEARANCE FOR SAW-CUTTING EQUIPMENT SUCH AS
- 16. IF OVER-REMOVAL OF HAUNCHES RESULTS, APPLY TWO COATS OF EPOXY RESIN TO EXPOSED DECK REINFORCING STEEL. ALL REASONABLE PRECAUTIONS SHALL BE TAKEN TO AVOID THIS CONDITION. REMOVAL OF THE CONCRETE HAUNCH OUTSIDE THE LIMITS OF THE LINK SLAB SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER LINEAR FOOT FOR ITEM 0974105A "CONCRETE HAUNCH REMOVAL". REMOVAL OF THE CONCRETE HAUNCH WITHIN THE LIMITS OF THE LINK SLAB SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD FOR ITEM 0503420 "REMOVAL OF CONCRETE DECK (BRIDGE)"

-	-	-	-	THE INFORMATION, INCLUDING ESTIMATED
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
-	-	-	-	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES
-	-	-	-	OF WORK WHICH WILL BE REQUIRED.
_	_		_	

REVISION DESCRIPTION

REV. DATE


SHEET NO. Plotted Date: 11/19/2014

A. STUER C. D'ANNUNZIO

SCALE AS NOTED



Filename: ...\S-12 - Deck Concrete Repairs.dgn



BLOCK:


REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 **OVER I-84 EB AND I-84 TR 833**

EAST HARTFORD


DECK

S-12 02.04.12 **CONCRETE REPAIRS**

042-305



(DRAWING NO. S-6 THRU S-10)



PROPOSED SECTION 1 AT PIERS (DRAWING NO. S-6 THRU S-10)

SCALE: $\frac{1}{2}$ " = 1'-0"

LINK SLAB NOTES:

REVISION DESCRIPTION

REV. DATE

- 1. LINK SLAB LENGTH = 11'-3" AT PIERS 1, 3 & 4, LINK SLAB LENGTH = 12'-0" AT PIER 2, LINK SLAB LENGTH = 10'-9" AT PIER 5, AND
- LINK SLAB LENGTH = 8'-9" AT PIER 6.

 2. WITHIN THE LINK SLAB LENGTH, ALL EXISTING SHEAR STUDS OR SPIRALS SHALL BE REMOVED. A DEBONDING MECHANISM SUCH AS NEOPRENE PADS SHALL BE PLACED BETWEEN THE TOP FLANGE AND THE PROPOSED DECK WITHIN THE LINK SLAB LENGTH.
- DUTSIDE OF THE LINK SLAB, KEEP EXISTING SHEAR STUDS OR REPLACE EXISTING
- SHEAR STUDS OR SPIRALS WITH SPACING AS SHOWN IN TABLE.

 5. PLACE PROPOSED LINK SLAB #6 BAR REINFORCMENT EVENLY BETWEEN EXISTING #4

 @ 9" LONGITUDINAL REINFORCEMENT. EXTEND PROPOSED REINFORCEMENT AS NEEDED
- TO PROPERLY DEVELOP BEYOND LINK SLAB LENGTH.

 6. THE LIMITS OF THE PROPOSED CONSTRUCTION ARE SYMMETRIC ABOUT THE CENTER LINE OF THE PIER EXCEPT AT PIER 6. IN ORDER TO REMOVE THE EXISTING #5 LONGITUDINAL BARS AT PIER 6, THE LIMITS OF CONSTRUCTION (MEASURED FROM THE CENTER LINE OF THE PIER) ARE TAKEN 8'-0" IN SPAN 6 AND 5'-6" IN SPAN 7.

SHEET NO. Plotted Date: 11/19/2014

DECK REMOVAL NOTES:

- 7. DURING THE REMOVAL OF THE EXISTING DECK IN THE VICINITY OF THE PROPOSED LINK SLAB, CARE SHALL BE TAKEN NOT TO DAMAGE EXISTING DECK REINFORCEMENT THAT IS DESIGNATED TO REMAIN.
- 3. AT EACH PROPOSED LINK SLAB LOCATION A MINIMUM OF ONE DECK SUPPORT PER BEAM IS REQUIRED AT EACH BEAM END.


SHEAR STUD NOTES:

Filename: ...\S-13 - Link Slab Details.dgn

- . CARE SHALL BE EXERCISED IN DEMOLITION OUTSIDE OF THE LINK SLAB TO MAINTAIN EXISTING SHEAR STUDS. SHEAR STUDS SHALL BE REPLACED IF DAMAGED DURING DEMOLITION.
- 10. LENGTHS OF STUDS SHALL BE IN INCREMENTS OF 1". MAXIMUM PERMISSIBLE LENGTH OF STUDS IS 8". IF THE STUD LENGTH REQUIRED IS IN EXCESS OF 8", THE REQUIRED LENGTH MAY BE OBTAINED BY STACKING.


BLOCK:

- 11. ACTUAL LENGTHS OR QUANTITIES OF STUDS WILL NOT BE GIVEN ON THE PLANS BUT SHALL BE DETERMINED BY THE CONTRACTOR IN ACCORDANCE WITH THE REQUIREMENTS SHOWN IN THE DETAILS.
- 12. REFER TO DRAWING NO. S-38 FOR DETAILS OF SHEAR STUDS AT SCUPPER.



SHEAR CONNECTOR DETAILS

SCALE: 1" = 1'-0"



LINK SLAB REINFORCEMENT DETAIL - TRANSVERSE SECTION

SCALE: $\frac{3}{4}$ " = 1'-0"

REPLACEMENT SHEAR STUD PITCH AT LINK SLAB							
STRINGER	MAX. PITCH OUTSIDE LINK SLAB						
S1	41/2"						
S2	4"						
S3	4 ½"						
S4	4 ½"						
S5	4"						
S6	4"						
S7	4"						
S8	4"						
S9	4"						
S10	4"						
S11	4 ¹ / ₂ "						
S12	4"						

LEGEND:


EXISTING CONCRETE, WEARING SURFACE AND MEMBRANE WATERPROOFING TO BE REMOVED

-	-	-	-	THE INFORMATION, INCLUDING ESTIMATED
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
-	-	-	1	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES
-	-	-	•	OF WORK WHICH WILL BE REQUIRED.
_	-	-	-	


A. STUER
CHECKED BY:
C. D'ANNUNZIO


SCALE AS NOTED





WN:	PROJECT NO.
	042-305
EAST HARTFORD	DRAWING NO.
RAWING TITLE:	S-13
	SHEET NO.
LINK SLAB DETAILS	02.04.13






SECTION

ELEVATION

STEEL WEB REPAIR DETAIL 1 (CORROSION < 5.25" HIGH)

SCALE: $1\frac{1}{2}$ " = 1'-0"



STEEL WEB REPAIR DETAIL 2 (CORROSION > 5.25" HIGH)


SCALE: $1\frac{1}{2}$ " = 1'-0"

				D
-	-	-	-	THE INFORMATION, INCLUDING ESTIMATED
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE C
-	-	-	-	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES
-	•	-	-	OF WORK WHICH WILL BE REQUIRED.
-	-	-	-	
REV.	DATE	REVISION DESCRIPTION	SHEET NO.	Plotted Date: 11/19/2014

SCALE AS NOTED



Filename: ...\S-15 - Steel Repair Details.dgn



BLOCK:

REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801

OVER I-84 EB AND I-84 TR 833

	EAST	HARTFORD
DRAWING	TITLE:	

S-15 02.04.15 STEEL REPAIR DETAILS

042-305

DRAWING NO.

STEEL WEB REPAIR NOTES:

- 1. THE CONTRACTOR SHALL FIELD VERIFY WEB SECTION LOSSES AFTER THE BEAM ENDS HAVE BEEN CLEANED AND BEFORE STEEL WEB REPAIR PLATES HAVE BEEN ORDERED. IF SECTION LOSSES DIFFER THAN THOSE NOTED IN 2013 ROUTINE INSPECTION REPORT, THE ENGINEER SHALL BE NOTIFIED IN ORDER TO EVALUATE IF ALTERNATE REPAIR DETAILS OR PLATE SIZES ARE NECESSARY.
- CONTRACTOR SHALL REMOVE ALL LOOSE PAINT, DEBRIS AND CORROSION FROM THE AREA OF THE EXISTING WEB WHERE THE COVER PLATE IS TO BE ATTACHED.
- USING THE FABRICATED WEB PLATE, CONTRACTOR SHALL DRILL HOLES IN WEB OF EXISTING STRINGER NECESSARY TO ATTACH WEB PLATES AND ANGLES. CONTRACTOR SHALL NOT USE CUTTING TORCH.
- CONTRACTOR SHALL PAINT ENTIRE CLEANED WEB AREA OF STRINGER,

PROPOSED WEB REPAIR PLATES

DETAIL

STRINGER

S2

S2

S9

S12

S12

S12

S12

S14

S14

S14

PIER

2

5

6

6

6

6

6

SPAN

3

6

6

6

7

7

WEB P

HEIGHT

10³/₄"

 $10^{3}/_{4}$ "

7³/₄"

7³/₄"

7³/₄"

 $11^{3}/_{4}$ "

 $7^{3}/_{4}$ "

 $7^{3}/_{4}$ "

7³/₄"

7³/₄"

WEB P

LENGTH

1'-6"

1'-6"

2'-0"

5'-6"

1'-6"

3'-0"

2'-0"

2'-0"


2'-0"


1'-6"


- CONTRACTOR SHALL ATTACH WEB PLATES AND ANGLES USING 0.875" DIAMETER HIGH STRENGTH BOLTS. BOTTOM LEG OF ANGLE SHOULD BE IN FULL CONTACT WITH THE TOP OF THE BOTTOM FLANGE.
- CONTRACTOR SHALL TIGHTEN ALL BOLTS, THEN WELD ALONG TOP LEG OF BOTH ANGLES TO FACE OF WEB PLATE.
- CONTRACTOR SHALL PROVIDE SEALANT AT ALL PLATE EDGES THAT ARE NOT WELDED.
- PAINT ALL PLATES, ANGLES AND BOLTS. WEB SECTION LOSSES THAT EXTEND HIGHER THAN 5 $\frac{1}{4}$ " ABOVE THE TOP OF THE BOTTOM FLANGE (EITHER SIDE) SHALL USE WEB REPAIR DETAIL 2, WHICH REQUIRES
- PARTIAL REMOVAL OF THE EXISTING $\frac{1}{2}$ " STEEL CONNECTION PLATE. THE EXISTING CONNECTION PLATES SHALL NOT BE CUT MORE THAN 4" ABOVE THE BOTTOM OF THE PLATE WITHOUT PERMISSION OF THE ENGINEER. CARE SHALL BE TAKEN DURING CUTTING NOT TO DAMAGE OR ADVERSELY AFFECT THE CONNECTION BETWEEN THE $\frac{1}{2}$ " PLATE AND THE END DIAPHRAGMS.
- 10. WEB REPAIR PLATE SIZES FOR DETAIL 2 ARE PROVIDED IN TABLE AND ARE BASED ON 1" MINIMUM SPACING BETWEEN THE CENTERLINE OF THE TOP ROW OF BOLTS AND THE LIMITS OF THE DETERIORATED STEEL. PLATE SIZES MUST BE ADJUSTED IF, AFTER STEEL IS CLEANED, EXTENTS OF SECTION LOSS IS GREATER THAN THAT PROVIDED IN THE 2013 ROUTINE INSPECTION REPORT (SEE NOTE 1).


STEEL COVER PLATE WELD NOTES:

1. ALL COVER PLATE END WELDS SHALL BE PEENED.









LEGEND:


REV. DATE

HOLLOW AREA (HA) SPALL AREA SPALL AREA WITH EXPOSED REBAR HAIRLINE CRACKS

SUBSTRUCTURE NOTES:

- EXISTING DIMENSIONS AND ELEVATIONS PROVIDED ARE FROM ORIGINAL CONSTRUCTION DRAWINGS AND SHALL BE FIELD
- SPALLED AND HOLLOW AREAS SHALL BE REMOVED AND REPAIRED. SEE TYPICAL CONCRETE REPAIR DETAILS ON DRAWING NO. S-25.
- AREAS OF CRACKING SHALL BE SEALED WITH EPOXY INJECTION CRACK REPAIR AND SHALL BE PAID FOR UNDER ITEM "EPOXY INJECTION CRACK REPAIR".
- SOUTH ELEVATION OF PIER SHOWN. NORTH ELEVATION HAS SIMILAR DEFICIENCIES. ENGINEER SHALL VERIFY DEFICIENCIES NOTED ON SOUTH FACE OF PIER PRIOR TO CONCRETE REPAIR OPERATION. ENGINEER SHALL ALSO DETERMINE LOCATIONS REQUIRING CONCRETE REPAIR AND LIMITS OF REPAIR ON NORTH FACE OF PIER PRIOR TO COMMENCEMENT OF CONCRETE REPAIR OPERATION. CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING SAFE ACCESS TO THE DETERIORATED AREAS.
- EXISTING GROUND ELEVATION IS SCALED FROM THE BRIDGE ELEVATION PROVIDED IN ORIGINAL CONSTRUCTION DRAWINGS PROJECT NO. 042-135 AND IS APPROXIMATE.

REVISION DESCRIPTION




PIER 1 ELEVATION - LOOKING NORTH SCALE: $\frac{1}{4}$ " = 1'-0"


EAST END ELEVATION SCALE: 1/4" = 1'-0"

-	-	-	1	THE INFORMATION, INCLUDING ESTIMATED
-	-	-		QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
-	-	-	-	INVESTIGATIONS BY THE STATE AND IS
-	-	-	-	IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITIES
-	-	-	-	OF WORK WHICH WILL BE REQUIRED.
-	-	-	-	


SHEET NO. Plotted Date: 11/19/2014


SCALE AS NOTED





PIER 1	SHEET NO. 02.04.19
ING TITLE:	S-19
EAST HARTFORD	042-305 DRAWING NO.
	PROJECT NO.





LEGEND:


HOLLOW AREA (HA)
SPALL AREA
SPALL AREA WITH EXPOSED REBAR
HAIRLINE CRACKS

SUBSTRUCTURE NOTES:

- 1. EXISTING DIMENSIONS AND ELEVATIONS PROVIDED ARE FROM ORIGINAL CONSTRUCTION DRAWINGS AND SHALL BE FIELD
- VERIFIED.

 2. SPALLED AND HOLLOW AREAS SHALL BE REMOVED AND REPAIRED. SEE TYPICAL CONCRETE REPAIR DETAILS ON DRAWING NO.
- 3. AREAS OF CRACKING SHALL BE SEALED WITH EPOXY INJECTION CRACK REPAIR AND SHALL BE PAID FOR UNDER ITEM "EPOXY INJECTION CRACK REPAIR".
- SOUTH ELEVATION OF PIER
 SHOWN. NORTH ELEVATION HAS
 SIMILAR DEFICIENCIES. ENGINEER
 SHALL VERIFY DEFICIENCIES NOTED
 ON SOUTH FACE OF PIER PRIOR
 TO CONCRETE REPAIR OPERATION.
 ENGINEER SHALL ALSO DETERMINE
 LOCATIONS REQUIRING CONCRETE
 REPAIR AND LIMITS OF REPAIR ON
 NORTH FACE OF PIER PRIOR TO
 COMMENCEMENT OF CONCRETE
 REPAIR OPERATION. CONTRACTOR
 SHALL BE RESPONSIBLE FOR
 PROVIDING SAFE ACCESS TO THE
- DETERIORATED AREAS.

 5. EXISTING GROUND ELEVATION IS SCALED FROM THE BRIDGE ELEVATION PROVIDED IN ORIGINAL CONSTRUCTION DRAWINGS PROJECT NO. 042-135 AND IS APPROXIMATE.




PIER 3 ELEVATION - LOOKING NORTH


SCALE: $\frac{1}{4}$ " = 1'-0"

EAST END ELEVATION

SCALE: $\frac{1}{4}$ " = 1'-0"

		DESIGNER/DRAFTER:	CONNECTION	SIGNATURE/	PROJECT TITLE:	TOWN:	PROJECT NO.
	THE INFORMATION, INCLUDING ESTIMA QUANTITIES OF WORK, SHOWN ON THE SHEETS IS BASED ON LIMITED	A. STUER CHECKED BY:	STATE OF CONNECTICUT	of CON	REHABILITATION OF BRIDGE	EAST HARTFORD	042-3 DRAWING NO.
	INVESTIGATIONS BY THE STATE AND I IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITI	C. D'ANNUNZIO	DEPARTMENT OF TRANSPORTATION	NO 224	Engineers, LLC 214 Lincoln Street NO. 02375 SR 500 TR 801	DRAWING TITLE:	S-2
	OF WORK WHICH WILL BE REQUIRED.	SCALE AS NOTED	DEFARTMENT OF TRANSFORTATION	Josha	OVER I-84 EB AND I-84 TR 833	DTED 2	02.04
EV. DATE REVISION DESCRIPTION	SHEET NO. Plotted Date: 11/19/2014		Filename:\FDP Drawings\S-21 - Pier 3.dgn	1		PIER 3	





LEGEND:

HOLLOW AREA (HA) SPALL AREA


SPALL AREA
SPALL AREA WITH EXPOSED REBAR
HAIRLINE CRACKS

SUBSTRUCTURE NOTES:

- 1. EXISTING DIMENSIONS AND ELEVATIONS PROVIDED ARE FROM ORIGINAL CONSTRUCTION DRAWINGS AND SHALL BE FIELD
- 2. SPALLED AND HOLLOW AREAS SHALL BE REMOVED AND REPAIRED. SEE TYPICAL CONCRETE REPAIR DETAILS ON DRAWING NO.
- S-25.

 3. AREAS OF CRACKING SHALL BE SEALED WITH EPOXY INJECTION CRACK REPAIR AND SHALL BE PAID FOR UNDER ITEM "EPOXY INJECTION CRACK REPAIR"
- INJECTION CRACK REPAIR".

 4. SOUTH ELEVATION OF PIER SHOWN. NORTH ELEVATION HAS SIMILAR DEFICIENCIES. ENGINEER SHALL VERIFY DEFICIENCIES NOTED ON SOUTH FACE OF PIER PRIOR TO CONCRETE REPAIR OPERATION. ENGINEER SHALL ALSO DETERMINE LOCATIONS REQUIRING CONCRETE REPAIR AND LIMITS OF REPAIR ON NORTH FACE OF PIER PRIOR TO COMMENCEMENT OF CONCRETE REPAIR OPERATION. CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING SAFE ACCESS TO THE DETERIORATED AREAS.
- 5. EXISTING GROUND ELEVATION IS SCALED FROM THE BRIDGE ELEVATION PROVIDED IN ORIGINAL CONSTRUCTION DRAWINGS PROJECT NO. 042-135 AND IS APPROXIMATE.



PIER 5 ELEVATION - LOOKING NORTH

SCALE: 1/4" = 1'-0"

EAST END ELEVATION

SCALE: $\frac{1}{4}$ " = 1'-0"

-	-	-	-	THE INFORMATION, INCLUDING ESTIMATED
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
-	-	-	1	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
-	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES
-	-	-	-	OF WORK WHICH WILL BE REQUIRED.
			_	


SHEET NO. Plotted Date: 11/19/2014


REVISION DESCRIPTION

REV. DATE

	DESIGNER/DRAFTER:
2	A. STUER
=	CHECKED BY:
	C. D'ANNUNZIO


SCALE AS NOTED





REHABILITATION OF BRIDGE	
NO.02375 SR 500 TR 801	DRAWIN
OVER I-84 EB AND I-84 TR 833	

EAST HARTFORD	042-305 DRAWING NO.
VING TITLE:	S-23
	02.04.23



<u>LEGEND</u>:

SPALL AREA


S-25.


DETERIORATED AREAS.


HOLLOW AREA (HA)


SUBSTRUCTURE NOTES:


		DESIGNER/DRAFTER:	A \$803 A	SIGNATURE/	PROJECT TITLE:	TOWN:	PROJECT NO.
	- THE INFORMATION, INCLUDING ESTIMATED	A. STUER		BLOCK:	DEHADILITATION OF BRIDGE		042-305
	SHEETS IS BASED ON LIMITED	CHECKED BY:		September 1	REHABILITATION OF BRIDGE	EAST HARTFORD	DRAWING NO.
	- INVESTIGATIONS BY THE STATE AND IS	C. D'ANNUNZIO	STATE OF CONNECTICOT	*	Engineers, LLC NO 0227E CD EOO TD 901	LASI HAKH OKD	
	THE CONDITIONS OF ACTUAL QUANTITIES		DEPARTMENT OF TRANSPORTATION	3 NO 22411	Engineers, LLC 214 Lincoln Street NO. 02375 SR 500 TR 801	DRAWING TITLE:	S-24
	OF WORK WHICH WILL BE REQUIRED.		DEPARTMENT OF TRANSPORTATION	1-5/100	OVER I-84 EB AND I-84 TR 833		SHEET NO.
	-	SCALE AS NOTED		J OH PORK	OVER I-84 EB AND I-84 TR 833	DTED 6	02.04.24
REV. DATE REVISION DESCRIPTION	SHEET NO. Plotted Date: 11/19/2014	1	Filename:\FDP Drawings\S-24 - Pier 6.dgn			PIER 6	

















2. ALL BACKWALL AND ABUTMENT REPAIRS SHALL BE COMPLETED PRIOR

TO JOINT INSTALLATION.

REMOVE BITUMINOUS CONCRETE OVERLAY AND MEMBRANE WATERPROOFING AND REPLACE WITH SILICONE JOINT SYSTEM. TO BE PAID FOR UNDER ITEM "SILICONE EXPANSION JOINT SYSTEM".

4. SILICONE FLEX JOINT SHALL BE INSTALLED WHEN THE AMBIENT TEMPERATURE IS BETWEEN 40° F AND 85° F.

APPROACH SLAB NOTES:

REVISION DESCRIPTION

REV. DATE

WHERE THE ANGLE BETWEEN THE CENTERLINE OF CONSTRUCTION AND THE ABUTMENT IS GREATER THAN 45 DEGREES, PLACE LONGITUDINAL REINFORCEMENT PARALLEL TO CENTERLINE OF CONSTRUCTION. OTHERWISE, PLACE LONGITUDINAL REINFORCEMENT PERPENDICULAR TO THE ABUTMENT. PLACE ALL TRANSVERSE REINFORCEMENT PARALLEL TO THE ABUTMENT.


SHEET NO. Plotted Date: 11/19/2014


40° F 1.39" 1.41" 45° F 1.45" 1.45" 50° F 1.50" 1.50" 55° F 1.55" 1.55" 60° F 1.59" 1.61" 65° F 1.64" 1.66" 70° F 1.68" 1.72" 75° F 1.73" 1.77" 80° F 1.77" 1.82" 85° F 1.82" 1.88"

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED. - | - | -- | - | -_ - -_ | _ | _

A. STUER C. D'ANNUNZIO


SCALE AS NOTED








BLOCK:

N:	PROJECT NO.
	042-305
EAST HARTFORD	DRAWING NO.
VING TITLE:	S-31
ABUTMENT	SHEET NO.
MODIFICATIONS 1	02.04.31











SCALE: 1'' = 1'-0''

SHEET NO. Plotted Date: 11/19/2014




PARAFFIN COATED JOINT AREA **EXISTING PARAFFIN JOINT DETAIL (WITH PROPOSED PARAPET CAP)**

SCALE: 1'' = 1'-0''



PROPOSED PARAFFIN JOINT DETAIL

SCALE: 1'' = 1'-0''



PROPOSED SECTION 20 (DRAWING NO. S-33)

SILICONE FLEX EXPANSION JOINT TREATMENT AT PARAPET AT NW CORNER

SCALE: 1'' = 1'-0''

PARAFFIN JOINT NOTES:

- 1. DO NOT CARRY LONGITUDINAL BARS THROUGH THE PARAFFIN JOINT COATED AREA. END THE REINFORCEMENT 2" CLEAR OF JOINT.
- 2. JOINT SHALL BE SQUARE TO FACE OF CURB.


-	-	-	-	THE INFORMATION, INCLUDING ESTIMATED
-	-	-	-	QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
-	-	-	-	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
_	-	-	-	THE CONDITIONS OF ACTUAL QUANTITIES
_	-	-	-	OF WORK WHICH WILL BE REQUIRED.
_	_	_	-	

REVISION DESCRIPTION


REV. DATE


SCALE AS NOTED






N:	PROJECT NO. 042-305
EAST HARTFORD VING TITLE:	DRAWING NO. S-34
MISC. DETAILS	02.04.34







PROPOSED HIGHWAY GUARDRAIL TRANSITION - SE ELEVATION SCALE: 1'' = 1'-0''

Filename: ...\S-36 - HGT Details 2.dgn

HIGHWAY GUARDRAIL TRANSITION NOTES:

REVISION DESCRIPTION

REV. DATE

1. FOR ADDITIONAL DETAILS AND NOTES, SEE DRAWING NO. S-37.

- MAINTAIN EXISTING #5 @ 12" (TYP.)


THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED

INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE

THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED.

SHEET NO. Plotted Date: 11/19/2014

STATE OF CONNECTICUT A. STUER C. D'ANNUNZIO **DEPARTMENT OF TRANSPORTATION** SCALE AS NOTED



REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 **OVER I-84 EB AND I-84 TR 833**

042-305 **EAST HARTFORD** HIGHWAY GUARDRAIL 02.04.36 **TRANSITION DETAILS 2**

S-36

EXISTING HIGHWAY GUARDRAIL TRANSITION - NW ELEVATION SCALE: 1'' = 1'-0''

MODIFIED APPROACH PARAPET

-EXISTING #6 @ 6" (FRONT FACE), EXISTING #5 @ 12" (BACK FACE)


> - CUT #5 @ 12" AND BEND DOWN (TYP.)

REMOVE PORTION OF


EXISTING CONCRETE PARAPET TO MODIFY


CURBLINE


REMOVE BRIDGE RAIL & CUT ANCHOR BOLTS @ TOP OF PARAPET (TYP.)





PROPOSED HIGHWAY GUARDRAIL TRANSITION - NW ELEVATION SCALE: 1" = 1'-0"













PIPE SUPPORT DETAIL



SECTION 32 SCALE: 1'' = 1'-0''



SCUPPER DOWNSPOUT SPLASH PAD SCALE: $\frac{1}{2}$ " = 1'-0"

 $\frac{3}{4}$ " x $\frac{3}{4}$ " CHAMFER (3 SIDES) ON EXPOSED EDGES (TYP.) ___ 3" CLR. - #4 BARS @ 12" EACH WAY ALTER. 4"X4"-D5/D5 (GR. 80) WELDED WIRE MAT

> **SECTION 33** SCALE: 1'' = 1'-0''

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED. - - -- | - | -- - -SHEET NO. Plotted Date: 11/19/2014 REVISION DESCRIPTION

A. STUER C. D'ANNUNZIO






BLOCK:

REHABILITATION OF BRIDGE NO. 02375 SR 500 TR 801 **OVER I-84 EB AND I-84 TR 833**

042-305 EAST HARTFORD S-39 **DRAINAGE** 02.04.39

DETAILS 2



DECK WEEPHOLE PLAN AT PIER

NOT TO SCALE NOT TO SCALE WATERPROOFING


- CUT HOLE IN

WATERPROOFING

MEMBRANE

TYPICAL DRAIN DETAIL

DECK WEEPHOLE DETAILS




SECTION THROUGH DECK WEEPHOLE AT BRIDGE FASCIA

SCALE: $\frac{1}{2}$ " = 1'-0"

DECK WEEPHOLE NOTES:

- THE COST OF FURNISHING AND INSTALLING $\frac{1}{4}$ " SQUARE GALVANIZED MESH SHALL BE INCLUDED IN THE CONTRACT BID PRICE FOR "HMA S0.25".
 - DECK WEEPHOLES SHALL ONLY BE REPLACED WITHIN THE LIMITS OF THE LINK SLAB.
- FLEXIBLE RUBBER HOSE WITH CLAMPS, $\frac{1}{2}$ " U BOLT WITH NUTS AND WASHERS AND 4" x $\frac{3}{8}$ " BENT PLATE SHALL BE PAID FOR UNDER ITEM "1
- /2" POLYVINYL CHLORIDE PLASTIC PIPE". 4. ALL DECK WEEPHOLES NOT LOCATED AT ABUTMENT SHALL BE PAID UNDER ITEM #0511211.




SCALE AS NOTED

Filename: ...\S-39 - Drainage Details 2.dgn


NOTES:

- 1. APPROACH SLABS SHALL BE TREATED OVERALL WITH MATERIAL FOR TACK COAT AND OVERLAID WITH $2\frac{1}{2}$ " HMA.
- 2. THE COST OF CUT AND JOINT SEALER SHALL BE INCLUDED IN THE PRICE FOR THE PRESSURE RELIEF JOINT.



PLAN AND GENERAL JOINT ARRANGEMENT

NOT TO SCALE



			DESIGNER/DRAFTER:	SIGNATURE/	PROJECT TITLE:	TOWN:	PROJECT NO.
-		- THE INFORMATION, INCLUDING ESTIMATED	A. STUER	BLOCK:			042-305
-		SHEETS IS BASED ON LIMITED	C D'ANNUNZTO STATE OF CONNECTICUT	SAMO OF	C&C Consulting	EAST HARTFORD	DRAWING NO.
		- INVESTIGATIONS BY THE STATE AND IS	C. D'ANNUNZIO STATE OF CONNECTICUT	*	Engineers, LLC NO. 02375 SR 500 TR 801	LASI HAKITOKE	─ S-40
_		- THE CONDITIONS OF ACTUAL QUANTITIES	DEPARTMENT OF TRANSPORTATION	A NO 22411	214 Lincoln Street INO. UZ3/3 SK SUU IK OUL	DRAWING TITLE:	3-40
-		_ OF WORK WHICH WILL BE REQUIRED.	SCALE AS NOTED DEPARTIFIED OF TRANSPORTATION	1-5 Manh	OVER I-84 EB AND I-84 TR 833		SHEET NO.
-		-	06/122 / 10 110 125	J Danking	OVER 1-04 ED AND 1-04 IK 033	PRESSURE RELIEF JOINT	- 02.04.40
RE∖	V. DATE REVISION DESCRIPTION	SHEET NO. Plotted Date: 11/19/2014	Filename:\S-40 - Pressure Relief Joint.dgn			PRESSURE RELIEF JOINT	